



EKB 500 – multi-function keyboard

Specifications

Keys: 48

Joystick: 30 PTZ function control

Jog/Shuttle: DVR control

Display: LCD 2 lines with 20 characters each

Baud rate: 1.200 ~ 38.400

Serial interfaces: RS-232 (service) / 2 x RS-485

Protocols: Pelco-P / Pelco-D / EverFocus / ED 2200 / ED 2250

Devices: control of speed dome and DVR

Cascading: up to 8 keyboards addressable

Wiring box: yes

Supported DVR models:

EDR 1640 / 1610 A/D / 920 / 910 A/D / 410 D

EDR 810 H / 810 M / 410 H / 410 M

EDSR 1600 / 900 / 600 / 400 H / 400 M / 100 H / 100 M

Power source: 12 V DC,
via included power supply 230 V AC

Power consumption: 10 W max.

Ambient temperature: 0°C ~ +40°C

Dimensions: 360 (W) x 110 (H) x 200 (D) mm

Weight: 1,5 kg

Features

- use of EEPbus for simultaneous control of DVRs and speed domes on one single RS-485 bus
- capable of controlling speed dome cameras and DVR
- 3D joystick control of PTZ function
- jog/shuttle DVR control
- matrix control (EverFocus DVR series' products)
- LCD display (20 x 2 lines), illuminated
- multi-protocol support (EverFocus, Pelco-P/D, ED 2200, ED 2250)
- password protection
- ergonomic button placement with sound indication for easy usage
- OSD access to connected devices
- two independent RS-485 communication ports with selectable baud rate
- camera /monitor mapping for easy reorganisation
- housing allows countersunk installation